

IN THE CLAIMS

1. **(Currently Amended)** A method for provisioning protection paths comprising:

determining network configuration information for a network formed by a plurality of nodes, wherein the network configuration information comprises topological information and timing information, wherein the topological information describes the interconnections between the nodes in the network, and wherein the timing information includes data regarding response times for the nodes in the network;

identifying a working path from a source node to a destination node spanning one or more intermediate nodes, wherein the source node, the destination node, and the intermediate nodes are all nodes in the network;

determining a timing constraint for failure recovery;

identifying potential nodes in the network that satisfy the timing constraint based on the network configuration information;

selecting a protection path from the source node to the destination node spanning a second set of one or more intermediate nodes, the second intermediate nodes selected from the potential nodes; and

setting up the protection path.

2. **(Canceled)**

3. **(Currently Amended)** The method of Claim 2 1, wherein the timing information indicates propagation delays for control messages passing between the nodes in the network and reconfiguration delays for the nodes in the network to reconfigure in the event of a failure recovery.

4. **(Original)** The method of Claim 3, wherein identifying the potential nodes that satisfy the timing constraint comprises identifying selected ones of the nodes in the network that can provide failure recovery within the timing constraint based upon the propagation delays and the reconfiguration delays.

5. **(Currently Amended)** The method of Claim 1, further comprising maintaining obligation information specifying a plurality of ~~failure~~ remote node obligations, each ~~failure~~ remote node obligation indicating, with respect to one of the nodes in the network, obligations of other ones of the nodes in the network given a failure of the one node.

6. **(Currently Amended)** The method of Claim 4 5, wherein identifying the potential nodes in the network that satisfy the timing constraint further comprises identifying the potential nodes in the network that satisfy the timing constraint based on the network configuration information and the ~~failure~~ remote node obligations.

7. **(Original)** The method of Claim 1, wherein determining the timing constraint comprises:

identifying a class of service associated with the working path; and
selecting the timing constraint based upon the class of service.

8. **(Original)** The method of Claim 1, wherein determining the timing constraint comprises receiving a configured value for the working path.

9. **(Original)** The method of Claim 1, wherein the network has a mesh topology, and wherein each of the nodes in the network comprises an optical network node.

10. **(Original)** The method of Claim 1, further comprising:
identifying a fault condition at a reporting one of the nodes in the network;
generating a fault message identifying the fault condition; and
broadcasting the fault message to all of the nodes in the network.

11. **(Original)** The method of Claim 1, wherein identifying the potential nodes that satisfy the timing constraint comprises determining selected ones of the nodes in the network that satisfy the timing constraint based upon a failure reported from any one of the source node, the destination node, and the intermediate nodes.

12. **(Currently Amended)** A computer readable medium storing logic for provisioning protection paths, the logic operable when executed by a computer to perform the steps of:

determining network configuration information for a network formed by a plurality of nodes, wherein the network configuration information comprises topological information and timing information, wherein the topological information describes the interconnections between the nodes in the network, and wherein the timing information includes data regarding response times for the nodes in the network;

identifying a working path from a source node to a destination node spanning one or more intermediate nodes, wherein the source node, the destination node, and the intermediate nodes are all nodes in the network;

determining a timing constraint for failure recovery;

identifying potential nodes in the network that satisfy the timing constraint based on the network configuration information;

selecting a protection path from the source node to the destination node spanning a second set of one or more intermediate nodes, the second intermediate nodes selected from the potential nodes; and

setting up the protection path.

13. **(Canceled)**

14. **(Currently Amended)** The computer readable medium of Claim ~~13~~ 12, wherein the timing information indicates propagation delays for control messages passing between the nodes in the network and reconfiguration delays for the nodes in the network to reconfigure in the event of a failure recovery.

15. **(Previously Presented)** The computer readable medium of Claim 14, the logic further operable when executed to identify the potential nodes that satisfy the timing constraint by identifying selected ones of the nodes in the network that can provide failure recovery within the timing constraint based upon the propagation delays and the reconfiguration delays.

16. **(Currently Amended)** The computer readable medium of Claim 12, the logic further operable when executed to maintain obligation information specifying a plurality of ~~failure~~ remote node obligations, each ~~failure~~ remote node obligation indicating, with respect to one of the nodes in the network, obligations of other ones of the nodes in the network given a failure of the one node.

17. **(Currently Amended)** The computer readable medium of Claim ~~12~~ 16, the logic further operable when executed to identify the potential nodes in the network that satisfy the timing constraint by identifying the potential nodes in the network that satisfy the timing constraint based on the network configuration information and the ~~failure~~ remote node obligations.

18. **(Previously Presented)** The computer readable medium of Claim 12, the logic further operable when executed to determine the timing constraint by:
identifying a class of service associated with the working path; and
selecting the timing constraint based upon the class of service.

19. **(Previously Presented)** The computer readable medium of Claim 12, the logic further operable when executed to determine the timing constraint by receiving a configured value for the working path.

20. **(Previously Presented)** The computer readable medium of Claim 12, wherein the network has a mesh topology, and wherein each of the nodes in the network comprises an optical network node.

21. **(Previously Presented)** The computer readable medium of Claim 12, the logic further operable when executed to perform the steps of:
identifying a fault condition at a reporting one of the nodes in the network;
generating a fault message identifying the fault condition; and
broadcasting the fault message to all of the nodes in the network.

22. **(Previously Presented)** The computer readable medium of Claim 12, the logic further operable when executed to identify the potential nodes that satisfy the timing constraint by determining selected ones of the nodes in the network that satisfy the timing constraint based upon a failure reported from any one of the source node, the destination node, and the intermediate nodes.

23. **(Currently Amended)** A network node comprising:

a network interface operable to couple to a network formed by a plurality of other nodes, wherein the network configuration information comprises topological information and timing information, wherein the topological information describes the interconnections between the nodes in the network, and wherein the timing information includes data regarding response times for the nodes in the network;

a memory maintaining network configuration information for the network;

a controller operable to:

identify a working path from the network node to a destination node spanning one or more intermediate nodes, wherein the destination node and the intermediate nodes are all other nodes in the network;

determine a timing constraint for failure recovery;

identify potential nodes in the network that satisfy the timing constraint based on the network configuration information;

select a protection path from the network node to the destination node spanning a second set of one or more intermediate nodes, the second intermediate nodes selected from the potential nodes; and

initiate setup of the protection path.

24. **(Canceled)**

25. **(Currently Amended)** The network node of Claim 24 23, wherein the timing information indicates propagation delays for control messages passing between the nodes in the network and reconfiguration delays for the nodes in the network to reconfigure in the event of a failure recovery.

26. **(Original)** The network node of Claim 25, wherein the controller is further operable to identify the potential nodes that satisfy the timing constraint by identifying selected ones of the nodes in the network that can provide failure recovery within the timing constraint based upon the propagation delays and the reconfiguration delays.

27. **(Currently Amended)** The network node of Claim 23, wherein the memory is further operable to maintain obligation information specifying a plurality of ~~failure~~ remote node obligations, each ~~failure~~ remote node obligation indicating, with respect to one of the nodes in the network, obligations of other ones of the nodes in the network given a failure of the one node.

28. **(Currently Amended)** The network node of Claim ~~23~~ 27, wherein the controller is further operable to identify the potential nodes in the network that satisfy the timing constraint further by identifying the potential nodes in the network that satisfy the timing constraint based on the network configuration information and the ~~failure~~ remote node obligations.

29. **(Original)** The network node of Claim 23, wherein the controller is further operable to determine the timing constraint by:
identifying a class of service associated with the working path; and
selecting the timing constraint based upon the class of service.

30. **(Original)** The network node of Claim 23, wherein the controller is further operable to determine the timing constraint by receiving a configured value for the working path.

31. **(Original)** The network node of Claim 23, wherein the network has a mesh topology, and wherein each of the nodes in the network comprises an optical network node.

32. **(Original)** The network node of Claim 23, wherein the controller is further operable to:

identify a fault condition at a reporting one of the nodes in the network;

generate a fault message identifying the fault condition; and

broadcast the fault message to all of the nodes in the network using the network interface.

33. **(Original)** The network node of Claim 23, wherein the controller is further operable to identify the potential nodes that satisfy the timing constraint by determining selected ones of the nodes in the network that satisfy the timing constraint based upon a failure reported from any one of the network node, the destination node, and the intermediate nodes.